PRODUCT INFORMATION

HUSKEYTM N-500 SERIES OILS

DESCRIPTION

HUSKEY N-500 SERIES OILS are a blend of highest quality selected paraffinic base oils coupled with the finest rust and oxidation resistant additives available. This unique combination produces an exceptional lubricating oil with excellent thermal stability and low carbon forming characteristics. Formulated with only highviscosity index oils to minimize viscosity changes during high and low temperature variations. These oils have extremely high film strength, to keep working metal parts separated, thus reducing friction and wear. Compounded to meet service requirements of Denison HF-2 and Cincinnati Milicrons high temperature heat stability test.

USAGE

HUSKEY N-500 SERIES OILS were designed primarily for all types of Air Compressors requiring nondetergent oils. These versatile oils are offered in several viscosity grades to meet the different needs of reciprocating, centrifugal and rotary compressors. Because of their anti-wear, anti-foam and excellent stability characteristics, they show outstanding performance when used as turbine oils, drip oils, hydraulic oils or general purpose lubricating oils.

ADVANTAGES

- Minimal Viscosity Change at Operating Temperatures
- Rust and Oxidation Protection
- Low Carbon Forming
- Compatible with Sealants and Painted Surfaces
- High Film Strength
- Reduces Friction and Wear
- Extends Equipment Life

TYPICAL SPECIFICATIONS

TEST	ASTM METHOD		RESULTS	
SAE Grade		10 wt.	20 wt.	30 wt.
ISO Grade		32	68	100
Pour Point, EF	D-97	-33	-25	-21
Flash Point, EF	D-92	432	475	502
Viscosity, sus @ 100EF	D-445	170	350	500
Viscosity, sus @ 210EF	D-445	46	57	65
Viscosity Index		102	100	100
Foam Test	D-892	Pass	Pass	Pass
Rust Test	D-665 A & B	Pass	Pass	Pass

PACKAGE AVAILABILITY

1 gal. Jugs (4/case), 5 gal. Pails 15 gal. Kegs and 55 gal. Drums

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office: 1580 Industrial Avenue, Norco, California 92860

(951) 340-4000 · Fax: (951) 340-4011 (888) 4-HUSKEY · www.huskey.com

Eastern Region Office: 8300 Corporate Park Drive, Macedonia, Ohio 44056 (330) 425-2567 · Fax: (330) 425-9637 (800) 238-LUBE